

FLUIDE II D



Fluid for automatic transmissions and hydraulic systems.

USES

- Automatic or semi-automatic transmissions and torque converters of passenger cars, light commercial vehicles and industrial vehicles, when the manufacturer requires an ATF (Automatic Transmission Fluid) GM DEXRON®-IID.
- Manual gear boxes when an ATF fluid is required.
- Hydrostatic transmissions.
- Power steering.
- Hydraulic systems when a fluid type GM DEXRON®-IID is required.

PROPERTIES

- Very high viscosity index linked with an excellent viscosity stability in operation.
- Very low pour point.
- Very good thermal stability.
- Excellent resistance to oxidation.
- Friction properties specific to the requirements of GENERAL MOTORS Hydramatic.

PERFORMANCES

Homologated:

- MAN 339 Type Z-1 & V-1
- VOITH H 55.633535
- ZF TE-ML 04D, 09, 14A, 17C
- MB-Approval 236.9

Meets the specifics requirements :

- GM DEXRON® IID
- FORD MERCON®

CHARACTERISTICS

FLUIDE II D	Unit	
Volumetric mass at 15°C	kg/m ³	870
Colour	-	Red
Viscosity at 40°C	mm ² /s	36.8
Viscosity at 100°C	mm ² /s	7.2
Viscosity index	-	163
Viscosity at -40°C	mPa.s	47500
Flash point Cleveland	°C	210
Pour point	°C	-44

The typical characteristics mentioned represent mean values.

TOTAL LUBRIFIANTS
562 avenue du Parc de L'île
92029 NANTERRE Cedex
France

FLUIDE II D
MARCH 2012
N° MPR 03/10



This lubricant, when used in accordance with our recommendations and for the application for which it is intended, does not constitute a special hazard. A safety data file conforming to the requirements of current EC legislation is available from your local trade consultant