


MULTIS MS 2



GREASE



TOTAL

Multi-Purpose, Extreme Pressure, Lithium/Calcium Grease with Molybdenum Disulfide.

APPLICATIONS

Multi-purpose, extreme pressure grease.
General lubrication.

SPECIFICATIONS

ADVANTAGES

Durable lubricant film.
Excellent adhesion to metal.

- **MULTIS MS 2** is a true multi-purpose grease, formulated for the lubrication of loaded slide, ball, and roller bearings, wheel bearings, universal joints, chassis, and various shock loaded or vibrating applications in transport, agriculture, and off-road equipment operating in wet, dusty, and/or dry conditions.
- **MULTIS MS 2** is suitable for use as a general purpose industrial grease requiring a NLGI grade 2, extreme pressure grease.
- Always avoid contamination of the grease by dust and/or dirt when applying. Preferably use a pneumatic pump system or cartridges.

- ISO 6743-9: L-XBCEB 2
- DIN 51502: MPF2K-25

- Replaces a wide range of greases.
- Miscible with most other conventional soap greases.
- Excellent adhesion to metal.
- Provides a durable lubricant film.
- Excellent mechanical and thermal stability.
- High resistance to temperature variations.
- Excellent anti-rust and anti-corrosion properties.
- Contains molybdenum disulfide.
- Does not contain lead or any other heavy metals harmful to humans or the environment.

TYPICAL CHARACTERISTICS	METHODS	MULTIS MS 2
Appearance	Visual	Smooth Gray
Operating Range, °F		-10 - 265
Thickener Type		Lithium / Calcium
NLGI Grade		2
Penetration Worked, 60xx	ASTM D 217	265 - 295
Dropping Point, °F	ASTM D 2265	365
Four Ball Weld Load, kg	DIN 51350-4	397
SKF-EMCOR anti-rust performance	DIN 51802	0-0
Base Oil Properties:		
Viscosity @ 40°C, cSt	ASTM D 445	150

TOTAL Lubricants USA, Inc.

Linden, NJ 07036
5 North Stiles Street
908.862.9300/800.526.4127

Rockingham, NC 28379
709 Airport Road
800.323.3198 / 800.526.4127

Knoxville, TN 37914
3315 Riverside Drive
800.323.3198 / 800.526.4127