

Product name: NEVASTANE SY 320 Page: 1/5

SDS n° :33556-33 Version :1.01 Version of : 2008-11-09

PRODUCT LABELS

LABELLING (standard or EU): Not concerned

R-phrases: None S-phrases: None

TRANSPORT LABELLING: Not applicable.

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY UNDERTAKING

Name of the product: NEVASTANE SY 320

Code No.: KKF

Product application: Lubricant for gears

Furnace chain oil (high temperature)

Supplier: TOTAL LUBRIFIANTS

562 avenue du Parc de l'Ile 92029 Nanterre CEDEX Tel: +33 (0)1 41 35 40 00 Fax: +33 (0)1 41 35 84 71

Emergency telephones: ORFILA / Tel: 01.45.42.59.59

See local details at end of sheet:

2. HAZARDS IDENTIFICATION

Health effects: Under normal conditions of use, the product holds no danger of intoxication

Environmental impact: Do not rejet this product into the environment

Physico-chemical hazards: No specific risk of fire or explosion under normal contitions of use

3. COMPOSITION/INFORMATION ON INGREDIENTS

PREPARATION

Chemical nature : The product is polyoxyalkylene glycol based.

Composition comments: Components contributing to hazards: None, to our knowledge

4. FIRST AID MEASURES

IN CASE OF SERIOUS OR PERSISTENT MANIFESTATIONS, CALL A DOCTOR OR EMERGENCY MEDICAL CARE.

Inhalation: Inhalation of heavy concentrations of vapour, fumes or spray, may cause mild

irritation of the throat.

Remove victim to fresh air and allow to rest.

Ingestion: Give nothing to drink

Do not induce vomiting to avoid the risk of aspiration into the respiratory tract.

Possible risk of vomiting and diarrhoea.

Skin contact: Immediately remove all soiled or stained clothing.

Wash the affected area immediately and repeatedly with soap and water.

Eye contact: Keep eyes open and rinse immediately and repeatedly with water for at least 15

minutes.



Product name: NEVASTANE SY 320 Page: 2/5

SDS n° :33556-33 Version :1.01 Version of : 2008-11-09

Aspiration: If the product is believed to have entered the lungs (in case of vomiting, for

example), take the person to hospital for immediate care.

5. FIRE FIGHTING MEASURES

See heading 9

Extinguishing media: - suitable:

Foam, carbon dioxide (CO2), powder.

- not recommended:

do not use water jets (stick jets) for extinguishing fire since they could help to

spread the flames.

Specific hazards: Incomplete combustion produces gases of varying toxicity such as CO, CO2 .These

may be highly dangerous if inhaled.

Protective measures for firefighters: Insulated breathing apparatus must be worn in confined premises with heavy

concentrations of fumes and gases.

6. ACCIDENTAL RELEASE MEASURES

See sections 8 and 13.

After spillage / leakage : - On the soil:

Surfaces on which the product has been spilled may become slippery. Do not allow the product to enter sewers or rivers or contaminate the soil. Recover with mechanical means such as pumps and skimmers. Contain and collect the spilled

product with sand or any other inert absorbant material.

- On water:

Floating absorbant material, then mechanical recovery. If the product is spilled in a river or in the sewers, notify the authorities of the possible presence of floating

items.

7. HANDLING AND STORAGE

HANDLING:

Prevention of user exposure: Ventilate extensively if the formation of vapours, fumes, mists or aerosol is a risk.

Make all the necessary arrangements in order to reduce exposure risk, notably to

products in use or to wastes.

Keep away from combustive substances; keep away from food and beverages.

Prevention of fire and explosion: Empty containers may contain flammable or explosive vapours.

There is a fire hazard associated with rags, paper or any other material used to

remove spills which become soaked with product.

Avoid accumulate of these: they are to be disposed off safely after use.

Precautions: Avoid static electricity build up with connection to earth.

Set up machinery and equipment so as to avoid the risk of accidental spills or splashes onto hot machine parts and electrical contacts (on joint failure, for

example).

STORAGE:

Technical measures: Make the necessary arrangements to prevent water and soil pollution.

Storage precautions: Store at room temperature, protected against contact with water and moisture, and

away from any source of ignition. Keep containers closed when not in use

- To be avoided:

Do not store exposed to the elements.

Incompatible products: A dangerous reaction may occur with strong oxidizing agents.



Product name: NEVASTANE SY 320 Page: 3/5

SDS n° :33556-33 Version :1.01 Version of : 2008-11-09

Packaging materials: - Recommended:

Use only containers, joints, pipes, etc...made in a material suitable for use with

water and glycol.

Keep in original container if possible.

Otherwise, transfer all indications on the regulatory label to the new container.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Technical measures:

Use the product in a properly ventilated atmosphere.

When working on enclosed place (tanks, reservoirs...), make sure that atmosphere is

not sufocating and/or wear recommend equipment.

Occupational exposure limit: None.

Hand protection: Glycol resistant gloves.

recommended material: nitrile, neoprene.

Polyvinyl chloride (PVC).

Eye protection: Goggles, in case of risk of splashing.

Skin and body (other than the hands) protection: Depending on requirements, face mask, boots, clothing proof against the product,

safety shoes (drum handling).

Don't wear ring, watch or similar thing which will be able to hold the product and

may give rise to some skin diseases.

Hygienic work practices: Avoid prolonged and repeated contact with the skin, especially with used or waste

product

If the product comes into contact with the skin, wash the affected area immediately

and copiously with soap and water. Use no abrasives, solvents or fuels.

Immediately remove all soiled or stained clothing. Do not use cloths stained with the product to dry hands.

Dont put the product-soaked rags in the pockets of working clothes.

Do not eat, drink or smoke while handling the product.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Liquid

Colour : Amber.

Odour : Mild.

Density/specific gravity: 1061 kg/m3

Temperature (°C) 20

Flash point : $> 240 \,^{\circ}$ C (ASTM D 93)

Température d'auto-inflammation : > 250 ° C (ASTM E 659)

Comments on autoignition temperature: This temperature may be significantly lower under particular conditions (slow

oxidation on finely divided materials...). Pour point: < -30 °C (ASTM D 97)

Solubility: - in water: Partially soluble.

Viscosity: 320 mm2/s

Temperature (°C) 40

10. STABILITY AND REACTIVITY

Stability: The product is stable at normal storage, handling and use temperatures.

Conditions to avoid: Heat (temperatures above flash point), sparks, ignition points, flames, static

electricity



Product name: NEVASTANE SY 320 Page: 4/5

SDS n° :33556-33 Version :1.01 Version of : 2008-11-09

Materials to avoid: Avoid contact with strong oxidizing

Hazardous decomp. products: Incomplete combustion and thermolysis produce quite toxic gases such as CO, CO2.

11. TOXICOLOGICAL INFORMATION

Acute toxicity / Local effect:

Inhalation, comments: Risk is improbable under normal conditions of use

Inhalation of important concentration of vapour or aerosols may cause irritation of

the upper respiratory tract.

Skin contact: dermal DL50 (Rabbit) > 5000 mg/kg

Skin contact, comments: Risk is improbable under normal conditions of use.

Ingestion : Oral DL50(Rat) > 5000 mg/kg

In case of ingestion of small quantities, no important effect observed. in case of

ingestion of larger amounts: abdominal pain, diarrhea, ...

CHRONIC TOXICITY OR LONG-TERM TOXICITY:

Skin contact: Characteristic skin affections (oil blisters) may develop following prolonged and

repeated exposure through contact with stained clothing

Sensitization: To our knowledge, the product does not a cause aggravated sensitivity.

12. ECOLOGICAL INFORMATION

Ecotoxicity : Biological oxygen demand, BOD. 21-24 @@@%@@@BOD20

LC50 96 hours Pimephales promelas > 1000 mg/l

Comments about ecotoxicity: It is considered to present a little danger for aquatic life.

no information available for used product

Mobility: - Ground:

Given its physical and chemical characteristics, the product generally shows little

mobility in the ground.

- Water:

Partially soluble

Persistence and degradability: The product should offer slow biodegradability

13. DISPOSAL CONSIDERATIONS

Waste disposal: Dispose of in a safe manner, in accordance with local regulations.

If need be, collection by an authorized waste contractor and regeneration or

incineration in an approved installation

Disposal of contaminated packaging: Proceed in compliance with the prevailing regulations.

National regulations: List of wastes: JOCE L349 of 16.02.2001.

Law No. 75-633 of 15.07.75 amended, relative to the elimination of wastes and the

recovery of materials.

Regulations concerning the collection of used oils:

Decree 79-981 of 21.11.79 and rules of 28.01.99 relative to their collection and the

conditions for their elimination.

Law No. 88-1261 of 30.12.88 concerning the import, export and transit of wastes. Decree No. 77-254 of 08.03.77 relative to the regulation for the dumping of oils and

lubricants into surface waters.



Product name: NEVASTANE SY 320 Page: 5/5

SDS n° :33556-33 Version :1.01 Version of : 2008-11-09

14. TRANSPORT INFORMATION

Not concerned by the transport regulations below.

Road (ADR) / Rail (RID):

Transport by barge (ADNR):

Marine (IMO-IMDG):

Air (ICAO/IATA):

15. REGULATORY INFORMATION

Not applicable

Risk phrases: None
Safety phrases: None

EU directives: Hazardous preparations directive 1999/45/EC modified (Directive 2001/60/EC).

Social Security code: Table of occupational illnesses and diseases No. 84

INVENTORIES:

JAPAN (ENCS):

All components on ENCS

PHILIPPINES (PICCS):

All components on TSCA

AUSTRALIAN (AICS):

All components on AICS

KOREA (ECL): Yes

16. OTHER INFORMATION

For France, in case of poisoning call the Antipoison Centre (if possible in your area) and/or the SAMU (15), see ORFILA number below Tel: Angers 02.41.48.21.21 - Bordeaux 05.56.96.40.80 - Lille 03.20.44.44.44 - Lyon 04.72.11.69.11 - Marseille 04.91.75.25.25 - Nancy 03.83.32.36.36 - Paris 01.40.05.48.48 - Rennes 02.99.59.22.22 - Strasbourg 03.88.37.37.37 - Toulouse 05.61.77.74.47 This sheet is in compliance with the standarts defined by the directives 91/155/CEE, 93/112/CEE, 2001/58/CE and the article 14 of the directive 1999/45/EC.

Revision date: 2008-11-09

* Information revised since the previous version of the SDS:

This safety data sheet serves to complete but not to replace the technical product sheets. The information contained herein is given in good faith and is accurate to the best of knowledge at the date indicated above. It is understood by the user that any use of the product for purposes other than those for which it was designed entails potential risk. The information given herein in no way dispenses the user from knowing and applying all provisions regulating his activity. The user bears sole liability for the precautions required when using the product. The regulatory texts indicated herein are intended to aid the user to fulfil his obligations. This list is not to be considered complete and exhaustive. It is the user's responsibility to ensure that he is subject to no other obligations than those mentioned.